

## RIZE 2XC - SPECIFICATIONS

**Print Technology:** Fused Filament Fabrication (FFF), Dual Nozzle

**Nozzle Diameter:** 0.4 mm

**Filament Diameter:** 1.75 mm

**Layer Thickness:** 0.05 ~ 0.4mm (50 ~ 400 $\mu$ )

**Build Size (WxDxH):** 8.9" X 7.9" X 11.8" (228mm x 200mm x 300mm)

**RIZE Materials:** Rizium GF, Rizium Carbon, Rizium Support

**Sindoh Materials:** PLA, ABS, Flexible, PVA (requires PVA nozzle)

**Open Materials:** Compatible

**Slicer Software:** Rize 2XC Slicer

**Workstation Compatibility:** Windows® 7 or above

**Connectivity and Ports:** USB Flash Drive, Ethernet, WiFi, USB Cable

**Smart Features:** Voice Assistant, Monitoring Camera, Color Touch Screen, Onboard Storage

**Convenience Features:** Auto Bed Levelling, Auto Nozzle Cleaning, Internal LED lights

**Printer Size (WxDxH):** 19.3" X 18.3" X 22.6" (490mm x 466mm x 573mm)

**Printer Weight:** 68.34lbs. (31kg); excluding cartridge

**Power requirements:** Universal power 100-240V AC, 350W

**Operating conditions:** 16°C – 29°C (61°F – 84°F) Environment Temperature; 20% - 70% RH

**Regulatory Compliance:** FCC, TUV and CE

**Special Facility Requirements:** None

**Warranty and Support:** 1 Year Standard Warranty, Phone/Internet Support included